

## SiC MOS P3M06025K3

### N-Channel Enhancement Mode



#### Features


- Qualified to AEC-Q101
- High Blocking Voltage with Low On-Resistance
- High-Frequency Operation
- Ultra-Small  $Q_{gd}$
- 100% UIS tested

#### Standards Benefits

- Improve System Efficiency
- Increase Power Density
- Reduce Heat Sink Requirements
- Reduction of System Cost

#### Applications

- Solar Inverters
- EV Battery Chargers
- High Voltage DC/DC Converters
- Switch Mode Power Supplies



TO-247-3

Gate	1
Drain	2
Source	3



#### Order Information

Part Number	Package	Marking
P3M06025K3	TO-247-3	P3M06025K3



## **Contents**

Features .....	1
Standards Benefits .....	1
Applications .....	1
Order Information .....	1
<b>Contents</b> .....	2
1. Maximum Ratings .....	3
2. Electrical Characteristics .....	4
3. Reverse Diode Characteristics .....	6
4. Thermal Characteristics .....	6
5. Typical Performance .....	7
6. Definitions .....	12
7. Package Outlines .....	13

PN Junction Semiconductor



## 1. Maximum Ratings

At  $T_J = 25^\circ\text{C}$ , unless specified otherwise

Parameter	Symbol	Value	Unit	Test Conditions
Drain - Source Voltage	$V_{DSmax}$	650	V	$V_{GS} = 0V$ $I_D = 100\mu A$
Gate - Source Voltage (dynamic)	$V_{GSmax}$	-8 / +20	V	AC ( $f > 1\text{ Hz}$ )
Gate – Source Voltage(static) turn-on gate voltage turn-off gate voltage	$V_{GS,on}$ $V_{GS,off}$	+15 -3	V	Static
Continuous Drain Current	$I_D$	97	A	$V_{GS} = 15V$ $T_C = 25^\circ\text{C}$
		69		$V_{GS} = 15V$ $T_C = 100^\circ\text{C}$
Pulsed Drain Current	$I_{D(pulse)}$	169	A	
Power Dissipation	$P_D$	440	W	
Operating Junction	$T_J$	-55 To +175	$^\circ\text{C}$	
Storage Temperature	$T_{stg}$	-55 To +175	$^\circ\text{C}$	
Solder Temperature	$T_L$	260	$^\circ\text{C}$	
Mounting Torque	$M_d$	1 8.8	Nm lbf-in	M3 or 6-32 screw



## 2. Electrical Characteristics

At  $T_J = 25^\circ\text{C}$ , unless specified otherwise

Parameter	Symbol	Value			Unit	Test Conditions
		Min.	Typ.	Max.		
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	650	/	/	V	$V_{GS} = 0V$ $I_D = 100\mu A$
Gate Threshold Voltage	$V_{GS(th)}$	1.8	2.4	/	V	(tested after 30ms pulse at $V_{GS} = 15V$ ) $V_{DS} = V_{GS}$ $I_D = 10mA$ $T_J = 25^\circ\text{C}$
		/	1.7	/	V	$V_{DS} = V_{GS}$ $I_D = 10mA$ $T_J = 175^\circ\text{C}$
Reverse Bias Drain Current	$I_{DSS}$	/	1	100	$\mu A$	$V_{GS} = 0V$ $V_{DS} = 650V$
Gate-Source Leakage Current	$I_{GSS}$	/	1	200	nA	$V_{GS} = 15V$ $V_{DS} = 0V$
Drain-Source On-State Resistance	$R_{DS(on)}$	/	25	33	m $\Omega$	$V_{GS} = 15V$ $I_D = 34A$ $T_J = 25^\circ\text{C}$
		/	29	/	m $\Omega$	$V_{GS} = 15V$ $I_D = 34A$ $T_J = 175^\circ\text{C}$
Transconductance	$g_{fs}$	/	28	/	S	$V_{DS} = 20V$ $I_{DS} = 40A$ $T_J = 25^\circ\text{C}$
		/	27	/	S	$V_{DS} = 20V$ $I_{DS} = 40A$ $T_J = 175^\circ\text{C}$
Input Capacitance	$C_{iss}$	/	5378	/	pF	$V_{GS} = 0V$ $V_{DS} = 400V$
Output Capacitance	$C_{oss}$	/	297	/	pF	$f = 1MHz$ $V_{AC} = 25mV$



# P3M06025K3 SiC MOS N-Channel Enhancement Mode

Parameter	Symbol	Value			Unit	Test Conditions
		Min.	Typ.	Max.		
Reverse Transfer Capacitance	$C_{rss}$	/	15.8	/	pF	$V_{GS} = 0V$ $V_{DS} = 400V$
Coss Stored Energy	$E_{oss}$	/	57	/	$\mu J$	$f = 1MHz$ $V_{AC} = 25mV$
Turn-on Energy	$E_{on}$	/	741	/	$\mu J$	$V_{DS} = 400V$ $V_{GS} = -3/15V$ $I_D = 50A$ $R_G = 1\Omega$
Turn-off Energy	$E_{off}$	/	127	/		
Turn-On Delay Time	$t_{d(on)}$	/	23	/	ns	$V_{DS} = 400V$ $V_{GS} = -3/15V$ $I_D = 50A$ $R_G = 1\Omega$
Rise Time	$t_r$	/	62	/		
Turn-Off Delay Time	$t_{d(off)}$	/	36	/		
Fall Time	$t_f$	/	9	/		
Internal Gate Resistance	$R_{G(int)}$	/	4.7	/	$\Omega$	$f = 1MHz$ $V_{AC} = 25mV$
Gate to Source Charge	$Q_{gs}$	/	47.4	/	nC	$V_{DS} = 400V$ $I_{DS} = 34A$ $V_{GS} = -3 \text{ to } 15V$ $I_G = 20mA$
Gate to Drain Charge	$Q_{gd}$	/	34.7	/		
Total Gate Charge	$Q_g$	/	146	/		



### 3. Reverse Diode Characteristics

At  $T_J = 25^\circ\text{C}$ , unless specified otherwise

Parameter	Symbol	Value		Unit	Test Conditions
		Typ.	Max.		
Diode Forward Voltage	$V_{SD}$	4.7	/	V	$V_{GS} = -3\text{V}$ $I_{SD} = 17\text{A}$ $T_J = 25^\circ\text{C}$
		4.1	/	V	$V_{GS} = -3\text{V}$ $I_{SD} = 17\text{A}$ $T_J = 175^\circ\text{C}$
Continuous Diode Forward Current	$I_S$	67	/	A	$V_{GS} = -3\text{V}$
Reverse Recover Time	$t_{rr}$	42	/	ns	$V_{GS} = -3\text{V}$ $I_{SD} = 50\text{A}$
Reverse Recovery Charge	$Q_{rr}$	254	/	nC	$V_R = 400\text{V}$ $dI/dt = 2000\text{A}/\mu\text{s}$
Peak Reverse Recovery Current	$I_{rrm}$	13	/	A	$T_J = 25^\circ\text{C}$

### 4. Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance from Junction to Case	$R_{\theta JC}$	0.34	$^\circ\text{C}/\text{W}$

## 5. Typical Performance

At  $T_J = 25^\circ\text{C}$ , unless specified otherwise




Figure 1. Output Characteristics  $T_J = -55^\circ\text{C}$




Figure 2. Output Characteristics  $T_J = 25^\circ\text{C}$




Figure 3. Output Characteristics  $T_J = 125^\circ\text{C}$




Figure 4. Output Characteristics  $T_J = 175^\circ\text{C}$




Figure 5. Normalized On-Resistance vs. Temperature




Figure 6. On-Resistance vs. Drain Current Various Temperatures



# P3M06025K3 SiC MOS N-Channel Enhancement Mode




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Transfer Characteristic for Various Junction Temperatures




Figure 9. Body Diode Characteristic at -55°C




Figure 10. Body Diode Characteristic at 25°C




Figure 11. Body Diode Characteristic at 125°C




Figure 12. Body Diode Characteristic at 175°C






Figure 13. Threshold Voltage vs. Temperature




Figure 14. Gate Charge Characteristics




Figure 15. 3rd Quadrant Characteristic at -55°C




Figure 16. 3rd Quadrant Characteristic at 25°C




Figure 17. 3rd Quadrant Characteristic at 125°C




Figure 18. 3rd Quadrant Characteristic at 175°C




Figure 19. Maximum Power Dissipation Derating vs. Case Temperature




Figure 20. Output Capacitor Stored Energy




Figure 21. Capacitances vs. Drain-Source Voltage (0 - 200V)




Figure 22. Capacitances vs. Drain-Source Voltage (0 - 650V)




Figure 23. Clamped Inductive Switching Energy vs. Drain Current (VDD= 400V)




Figure 24. Clamped Inductive Switching Energy vs.  $R_{G(ext)}$



# P3M06025K3 SiC MOS N-Channel Enhancement Mode




Figure 25. Clamped Inductive Switching Energy vs. Temperature




Figure 26. Switching Times vs.  $R_{G(ext)}$




Figure 27. Transient Thermal Impedance (Junction - Case)




Figure 28. Safe Operating Area

PN Junction Semiconductor

## 6. Definitions




Figure 29. Turn-off Transient Definitions




Figure 30. Turn-on Transient Definitions




Figure 31. Reverse Recovery Definitions





Figure 32.  $V_{GS}$  Transient Definitions

PN Junction Semiconductor

## 7. Package Outlines



SYMBOL	DIMENSIONS			NOTES
	MIN.	NOM.	MAX.	
A	4.83	5.02	5.21	
A1	2.29	2.41	2.55	
A2	1.50	2.00	2.49	
b	1.12	1.20	1.33	
b1	1.12	1.20	1.28	
b2	1.91	2.00	2.39	6
b3	1.91	2.00	2.34	
b4	2.87	3.00	3.22	6, 8
b5	2.87	3.00	3.18	
c	0.55	0.60	0.69	6
c1	0.55	0.60	0.65	
D	20.80	20.95	21.10	4
D1	16.25	16.55	17.65	5
D2	0.51	1.19	1.35	
E	15.75	15.94	16.13	4
E1	13.46	14.02	14.16	5
E2	4.32	4.91	5.49	3
e	5.44BSC			
L	19.81	20.07	20.32	
L1	4.10	4.19	4.40	6
ϕP	3.56	3.61	3.65	7
ϕP1	7.19REF.			
Q	5.39	5.79	6.20	
S	6.04	6.17	6.30	

Drawing and Dimension

PN Junction Semiconductor



## Important Notice

---

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, PN Junction hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

PN Junction reserves the right to make changes at any time to any products or information herein, without notice. “Typical” parameters which may be provided in PN Junction data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typical” must be validated for each customer application by customer’s technical experts.

In addition, any information given in this document is subject to customer’s compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer’s products and any use of the product of PN Junction in customer’s applications. The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer’s technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest PN Junction office ([www.pnjsemi.com](http://www.pnjsemi.com)).

## Warnings

---

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest PN Junction office.

Except as otherwise explicitly approved by PN Junction in a written document signed by authorized representatives of PN Junction, PN Junction’s products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.